

samaritan® PAD 450P



Public Access Defibrillator with Integrated CPR Rate Advisor™

The confidence and power to save a life.

While some cardiac events are treatable with effective Cardiopulmonary Resuscitation (CPR) alone, others require a combination of effective CPR and the use of an automated external defibrillator (AED) to deliver a lifesaving shock within the first few minutes of sudden cardiac arrest (SCA). In both cases, effective CPR contributes to an increase of survival rates of up to 75%.

More than a simple AED, HeartSine's samaritan PAD 450P with integrated CPR Rate Advisor™ provides real-time visible and audible feedback to the rescuer on the rate of CPR compressions during an SCA resuscitation.





Real-Time CPR Rate Feedback

ICG-Based Feedback. With its revolutionary technology, HeartSine's proprietary CPR Rate Advisor uses only the defibrillator electrodes to determine the rate of CPR being applied, without the addition of accelerometers (or pucks) commonly used in other AED solutions.

Easy-to-Follow Visual and Verbal Guides. Easy-to-understand visual and voice prompts guide a user through the entire CPR process, providing specific feedback on the rate of compressions.

Improved CPR Fraction. To ensure that CPR is consistently delivered, the SAM 450P continues to remind the rescuer to perform CPR when no CPR is detected.



No CPR being performed/"Begin CPR"

"Push Faster"

"Good Speed"

"Push Slower"


Visual indicators and audible feedback tell the rescuer if the rate of CPR is in line with the AHA guidelines.

Ready to Shock

Highest level of protection from dust and water. With its IP56 rating, the SAM 450P defibrillator offers unmatched ruggedness for a variety of environments.

Advanced technology. The SAM 450P utilizes proprietary electrode technology and SCOPE™* biphasic technology, an escalating and low-energy waveform that automatically adjusts for patient impedance differences, to assess rhythm and recommend defibrillation if necessary.

Most compact design. At 2.4 lbs and with a compact footprint, the SAM 450P is the most portable AED on the market.



* Self-Compensating Output Pulse Envelope technology automatically optimizes the waveform pulse envelope (amplitude, slope, and duration) for each individual patient.

Real Economy for the Real World

Two parts, one expiration date. Pad-Pak™ cartridge combines battery and electrode pads, with only one expiration date to monitor.


Low cost of ownership. With a shelf life of four years from date of manufacture, the Pad-Pak offers significant savings over other defibrillators that require separate battery and electrode replacements.



Pad-Pak and Pediatric-Pak with pre-attached electrodes.

The HeartSine PAD's built-in intelligence and unique pediatric Pad-Pak ensure the appropriate energy level is delivered for children.

CPR Rate Advisor is deactivated when the Pediatric-Pak is in use.



| Physical | With Pad-Pak™ Inserted |
|----------|--|
| Size: | 8.0 in x 7.25 in x 1.9 in/20 cm x 18.4 cm x 4.8 cm |
| Weight: | 2.4 lbs/1.1 kg including Pad-Pak Battery |

| Defibrillator | |
|---------------|---|
| Waveform: | Self-Compensating Output Pulse Envelope (SCOPE™) Biphasic waveform. Optimized biphasic escalating waveform compensates energy, slope and envelope for patient impedance |

| Patient Analysis System | |
|--------------------------|---|
| Method: | Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required |
| Sensitivity/Specificity: | Meets ISO 60601-2-4 and AAMI DF80 |

| Environmental | |
|---------------------------------------|---|
| Operating/Standby Temperature: | +32°F to +122°F/0°C to 50°C |
| Temporary Transportation Temperature: | 14°F to 122°F/-10°C to 50°C for up to two days. Unit must be returned to standby/operating temperature for 24 hours before use. |
| Relative Humidity: | 5% to 95% (non-condensing) |
| Water Resistance: | IEC 60529/EN 60529 IP56 |
| Altitude: | 0 to 15,000 feet/0 – 4,575 meters |
| Shock: | MIL STD 810F Method 516.5, Procedure I (40 G's) |
| Vibration: | MIL STD 810F Method 514.5+ Category 4 Truck Transportation – US Highways Category 7 Aircraft – Jet 737 & General Aviation |
| EMC: | EN 60601-1-2 |
| Radiated Emissions: | EN55011 |
| Electrostatic Discharge RF Immunity: | EN61000-4-3 80MHZ-2.5GHZ (10 V/m) |
| Magnetic Field Immunity: | EN61000-4-8 (3 A/m) |
| Aircraft: | RTCA/DO-160F, Section 21 (Category M) |
| Falling Height: | 3.3 feet/1 meter |

| Energy Selection | | | |
|------------------|----------------|----------------|---------------|
| Adult: | Shock 1: 150J; | Shock 2: 150J; | Shock 3: 200J |
| Pediatric: | Shock 1: 50J; | Shock 2: 50J; | Shock 3: 50J |

| Charging Time | |
|---------------------|---|
| New Battery: | Typically 150J in < 8 seconds, 200J in < 12 seconds |
| After 6 Discharges: | Typically 150J in < 8 seconds, 200J in < 12 seconds |

| Event Documentation | |
|------------------------|---|
| Type: | Internal Memory |
| Memory Capacity: | 90 minutes of ECG (full disclosure) and event/incident recording |
| Playback Capabilities: | Custom USB cable directly connected to PC and Saver EVO™ Windows-based data review software |

| Materials Used | |
|----------------|---|
| Housing: | ABS, Santoprene |
| Electrodes: | Hydrogel, Silver, Aluminium and Polyester |

| Pad-Pak – Electrode and Battery Cartridge | |
|--|--|
| Adult Pad-Pak (Pad-Pak-01) and Pediatric Pad-Pak (Pad-Pak-02) <i>*ETSO certified Pad-Pak also available</i> | |
| Shelf Life: | 4 years from manufacture date |
| Weight: | 0.44 lbs/0.2 kg |
| Size: | 3.93 in x 5.24 in x .94 in/10 cm x 13.3 cm x 2.4 cm |
| Battery Type: | Lithium Manganese Dioxide (LiMnO ₂) |
| Capacity: | > 60 shocks at 200J 18V, 1.5 Amp Hrs |
| Electrodes: | HeartSine samaritan disposable defibrillation pads are supplied as standard with each device |
| Placement: | Anterior-lateral (Adult); Anterior-posterior (Pediatric) |
| Active Gel Area: | 15.5 in ² /100 cm ² |
| Cable Length: | 3.3 feet/1 meter |

EMEA/APAC
HeartSine Technologies, Ltd.
203 Airport Road West
Belfast, Northern Ireland
BT3 9ED
Tel: +44 28 9093 9400
Fax: +44 28 9093 9401
info@heartsine.com



U.S./Americas
HeartSine Technologies, Inc.
121 Friends Lane, Suite 400
Newtown, PA 18940
Toll Free: (866) 478 7463
Tel: +1 215 860 8100
Fax: +1 215 860 8192
info@heartsine.com



UL Classified. See complete marking on product.

CAUTION: U.S. Federal law restricts this device to sale by or on the order of a licensed practitioner.

© 2015 HeartSine Technologies, Inc. All rights reserved.
H009-041-001-0

Lifesaving, Pure and Simple



www.heartsine.com

